



OLYMPIC®

43887, 43888

## OLYMPIC® Premium Interior Fast Dry Varnish

## GENERAL DESCRIPTION

OLYMPIC® Premium Interior Fast Dry Varnish is an alkyd varnish designed to deliver professional results. It is recommended for interior applications such as woodwork, paneling, or any wood surface where extra durability and abrasion resistance is desired. As part of a one day wood finishing system, it can be used in conjunction with the OLYMPIC Fast Dry Stains.

## PRODUCT INFORMATION

43887	Clear Satin
43888	Clear Gloss

Do not tint.

## RECOMMENDED SUBSTRATES

Doors  
Furniture  
Trim  
Cabinets

## FEATURES / BENEFITS

Professional Fast Dry Varnish  
Alkyd/Oil Based  
Abrasion Resistant  
For Woodwork and Paneling  
3 Hour Recoat

## DIRECTIONS FOR USE

Stir thoroughly before use. DO NOT SHAKE.

## APPLICATION INFORMATION

**Application Equipment:** Apply with a high quality brush, paint pad, or by spray equipment.

**Application Method:** Always apply in thin coats with the grain of the wood using a smooth, even stroke.

**Thinning:** No thinning is needed.

## PRODUCT DATA

<b>PRODUCT TYPE:</b>	Alkyd Resin
<b>GLOSS:</b>	43887 Satin: 37 to 43 (60° Gloss Meter) 43888 Gloss: 93 to 98 (60° Gloss Meter)
<b>VOLUME SOLIDS:</b>	46% +/- 2%
<b>WEIGHT SOLIDS:</b>	49% +/- 2%
<b>VOC:</b>	<550 g/L (4.58 lbs./gal.)
<b>WEIGHT/GALLON:</b>	7.3 lbs. (3.3 kg) +/- 0.2 lbs. (91 g)
<b>FLASH POINT:</b>	50°F (10°C)

**COVERAGE:** Approximately 535 sq. ft. (49.6 sq. meters) per gallon (3.78L). Coverage will vary with wood type, porosity, preparation and application.

Wet Film Thickness:	3.0 mils
Wet Microns:	76.2

Dry Film Thickness:	1.4 mils
Dry Microns:	35.6

**DRYING TIME:** Dry times are affected by humidity, temperature, film build, and moisture content of the wood. Allow a minimum of 3 hours drying time before recoating. Dries to touch in 45 minutes and to handle in 1 1/2 hours. Allow 8-24 hours dry time before general use.

**CLEANUP:** Clean up with mineral spirits or paint thinner.

Danger - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

## OLYMPIC® Premium Interior Fast Dry Varnish

## GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the OLYMPIC limited warranty to apply. Varnish only clean, dry, sound surfaces. Scrape off loose varnish and sand smooth. Sand old glossy surfaces until dull.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**NEW SURFACE:** Apply one or more coats of OLYMPIC Premium Interior Fast Dry Varnish as necessary for adequate protection.

**REFINISH:** Spot coat worn areas with OLYMPIC Premium Interior Fast Dry Varnish and finish with one or two complete finish coats.

**FOR BEST RESULTS:** Allow a minimum of 3 hours drying time between coats. To ensure a smooth finish, lightly sand the surface with 200 grit or finer sandpaper or 000 steel wool prior to applying the next coat. Clean the sanding dust from the surface using a tack cloth or vacuum cleaner.

## LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Do not apply when the air, coating or surface temperature is below 50°F (10°C).

These products are not intended for immersion service or other extreme conditions. Not recommended in situations characterized by high heat or presence of corrosive chemicals nor for use on floors.

## PACKAGING

Available in 1-Gallon (3.78L) and 1-Quart (946 mL) containers.

## SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

Explosion-proof equipment must be used when coating with these materials in confined areas. Keep containers closed and away from heat, sparks, and flame when not in use.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.ppgpittsburghpaints.com](http://www.ppgpittsburghpaints.com)  
[www.ppgporterpaints.com](http://www.ppgporterpaints.com)

Technical Services  
1-800-441-9695

Architect/Specifier  
1-888-PPG-IDEA

PPG Canada, Inc.  
Architectural Coatings  
4 Kenview Blvd  
Brampton, ON L6T 5E4

T.D. 4029 10/2011  
(Supersedes 5/2008)

Made in the  
**USA**