



Architectural Coatings

PITT BULL® Interior/Exterior Premium Spray Enamel

GENERAL DESCRIPTION

Our premium aerosol spray products permit the user to achieve a quick, dry, smooth, durable finish comparable to brush application in a variety of ready-mixed and safety colors and primers with rust control, stain killing properties. They are available in gloss, satin or flat finishes. The finish coats are a distinctive quick dry formulation that resist household solvents as well as grease and oil.

RECOMMENDED SUBSTRATES

Metal
Wood

APPLICATION INFORMATION

Cover floor and equipment where spray might settle. Shake can for at least 1 minute, listening for rattle of mixing ball. During application, shake intermittently for approximately 10 seconds at 1 to 2 minute intervals. Press valve all the way down. Do not extend finger beyond the valve. Hold container about 6 to 8 inches from surface to be sprayed. Do not cover with continuous spray. Move back and forth, releasing spray head after each stroke. Overlap each stroke. Apply 2 thin coats rather than 1 heavy coat. If paint runs or sags, paint is being applied too heavily, or container is too close to surface.

If spray button becomes clogged, pull off and clean with paint thinner. DO NOT stick pins or wire into can opening. Replace spray button firmly, with valve opening pointing away from you. After use, invert can and spray for 4 seconds to clean valve.

KEEP OUT OF REACH OF CHILDREN. Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

USE IN A WELL VENTILATED AREA ONLY. USE ONLY AS DIRECTED. When using indoors, keep windows and doors open until fumes dissipate.

Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	65 to 100°F	18 to 38°C
Substrate:	65 to 100°F	18 to 38°C

PRODUCT INFORMATION

Premium Spray Enamels

55-602	Brilliant Yellow
55-605	Ivy Green
55-606	Vista Green
55-607	Battleship Gray
55-608	Gold
55-609	Gloss Black
55-610	Silver
55-611	Gloss White
55-612	Flat Black
55-617	Flat White
55-618	Clear Acrylic
55-621	Autumn Brown
55-624	Safety Red
55-626	Safety Blue
55-627	Safety Green
55-628	Safety Orange
55-630	Safety Yellow
55-631	BBQ/Stove Black
55-652	Almond
55-663	Bright White

PRODUCT DATA

PRODUCT TYPE:	Enamel Spray Paint
SHEEN:	Flat, Satin, Gloss
VOC:	60% Max. 1.2 g O ₃ /g product max

DRYING TIME: Dry time @77°F (25°C); 50% relative humidity.

For best results, spray at room temperature, 68° to 78°F (20° to 26°C). To prevent wrinkling or lifting, recoat within 2 hours or wait 5 days until thoroughly dry.

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

CLEANUP: High quality paint thinner

DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. Refer to www.pppittsburghpaints.com, Spontaneous Combustion Advisory for additional information.

STORAGE: STORE OUT OF DIRECT SUNLIGHT. Prevent this container from coming in contact with water for a prolonged period of time. Always keep container in a cool, dry place.

DISPOSAL: Discard empty can in trash pickup. DO NOT place in home garbage compactor or burn.

FEATURES / BENEFITS

Features

Fast drying
Excellent hiding
Easy application

Benefits

Recoats in less than 2 hours
Provides better surface coverage
Ideal for touch up and smaller scale projects

GENERAL SURFACE PREPARATION

Surfaces to be coated must be dry, clean, sound, and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, mildew, rust, product fines, and dust. Remove loose paint, by wire brushing, scraping, sanding, and/or pressure washing. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Feather back all rough edges to sound surface by sanding. Use a drop cloth or newspapers to protect surrounding areas from spray mist.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

LIMITATIONS OF USE

DO NOT STICK PIN OR OTHER OBJECT INTO THE CAN. Contents under pressure. DO NOT PUNCTURE, INCINERATE (BURN), COMPACT OR STORE ABOVE 120°F (49°C). STORE OUT OF DIRECT SUNLIGHT. Exposure to heat or prolonged exposure to sun may cause bursting.

Do not use on surfaces that come into contact with food.

PACKAGING

Aerosol Net Wt. 11.75 oz. (333 g)

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpittsburghpaints.com
www.ppgporterpaints.com

Technical Services
1-800-441-9695
1-888-807-5123 fax

Architect/Specifier
1-888-PPG-IDEA

PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

A3.21 10/2011
(Supersedes 8/2010)

**Made in the
USA**