

Architectural Coatings

Liquid Nails Tub Surround Advanced Interior/Exterior Construction Adhesive

GENERAL DESCRIPTION

Liquid Nails Tub Surround Advanced, LN-1015, is an ultra-durable, hybrid polymer adhesive that features same day sealing technology; enabling professionals to seal and finish their installation in the same day while homeowners can enjoy their newly installed tub or shower surround more quickly. This unique formulation meets requirements of all air quality regulations. Certified by UL Environment to meet *GREENGUARD Gold* Standard as a low emitting material.

RECOMMENDED SUBSTRATES

Recommended For Bonding Most Plastic And Fiberglass Tub & Shower Surrounds To: Drywall, Wood, Plywood, Fiberglass, Ceramic Tiles, Greenboard, and Cement Backerboard

FEATURES / BENEFITS

- Same Day Sealing Technology - Seal Around Tub Surround Immediately After Installation
- Hybrid Technology - Bonds Almost Everything
- Strong Initial Hold - No Bracing Required
- No Burn Through
- Strong, Waterproof Bond

CONFORMANCE STANDARDS

VOC compliant in all regulated areas



PRODUCT INFORMATION / PACKAGING

LN-1015 9.0 FL OZ (266 mL) Tube (12 Tubes/Carton)

PRODUCT DATA

- BASE:** Hybrid
 - COLOR:** White
 - APPEARANCE:** Smooth paste
 - APPLICATION TEMPERATURE:** 0°F to 140°F (-17°C to 60°C)
 - SERVICE TEMPERATURE:** -40°F to 300°F (-40°C to 149°C)
 - SAG (ASTM D2202):** <0.10"
 - SHEAR STRENGTH:** 24 hours – 400psi (full strength)
 - WEIGHT PER GALLON:** 12.2 lbs. (5.53 kg)
 - VISCOSITY:** 500,000 cps
 - OPEN TIME:** 20 minutes at room temperature
 - MINIMUM CURE TIME:** 24 hours at room temperature
 - FREEZE/THAW STABILITY:** No effect after 5 cycles
 - FLAMMABILITY:** Non-flammable
 - PERCENT VOLATILE:** < 3%
 - COVERAGE:** Approximately 28 linear ft. (8.5 linear meters) using a ¼" (6 mm) bead. A typical surround will require approximately 3 tubes of adhesive for installation.
 - SHELF LIFE:** One year from date of purchase
 - ODOR:** Slight
 - SPECIFICATIONS:** Exceeds ASTM C557
 - MAX VOC:** < 1.5% by weight
- LIMITATIONS OF USE**
- Not recommended for polyethylene, polypropylene, Teflon, EPDM, or TPO.
- FREEZE/THAW STABLE. Store product at 40°F (4°C) to 100°F (38°C).

Read Label and Safety Data Sheet Prior to Use. See other cautions on last page.

GENERAL SURFACE PREPARATION/APPLICATION

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

DIRECTIONS: For applications over ceramic tile, sand surface before applying adhesive. Unscrew nozzle, cut tip of cartridge, replace nozzle and cut to required bead size. Insert into cartridge gun. Apply adhesive to surround panel in a ¼ inch (6 mm) wide continuous bead approximately one inch (2.5 cm) from the edges of the panel. An "S" or "X" shaped bead may be applied to the center portion of the panel. Press the panel into place on the wall within 10 minutes of the adhesive application. Repeat for remaining panels and corner units. Bracing may be needed if panels do not lie flat. Panel edges and seams may be caulked and sealed immediately after installation. Allow adhesive and caulk to dry overnight prior to use.

CLEANUP: Dry cloth when wet, scraping and mineral spirits when dry.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product.

PERMISSIBLE TEMPERATURES DURING APPLICATION:

Material:	40 to 100°F	4 to 38°C
Ambient:	0 to 140°F	-17°C to 60°C
Substrate:	0 to 140°F	-17°C to 60°C

PRECAUTIONS

WARNING! HARMFUL IF SWALLOWED. CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust or particulates arising from the application of this preparation. Use personal protective equipment as required. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

© 2022 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Liquid Nails is a registered trademark of PPG Architectural Finishes, Inc. UL Greenguard is a certification mark of UL LLC.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.

