



## Highlights

PPG's Enviracryl™ and Envirocron™ powder coatings are aesthetically pleasing, produce a durable uniform finish and can be custom formulated with finishes from high gloss to low gloss, and in a variety of textures.

PPG's "World Class" Ultradurable Polyester Powder Coatings provide a combination of good physical and chemical resistance properties with excellent resistance to outdoor weathering. This extensive line of Polyester Powders is manufactured to meet the increasing requirement demands of the appliance and industrial markets. These sophisticated Polyesters are the solution to your smoothness, low-bake, durability and physical property requirements. An unsurpassed application development program enables consistently friendly use on a variety of substrates.

## Product Features

- Available in a wide range of colors and glosses
- Excellent Exterior durability
- Good chemical resistance
- Out gas friendly
- Specifically formulated to meet the requirements of AAMA 2604

## Technical Properties

Property	Test Method	Value
Color	_____	Coarse Metallic PTBB5000
Appearance		Metallic
Gloss	ASTM D-523	80 Minimum @ 60°
Adhesion	ASTM D-3359	Dry: 100% (5B Pass) Wet: 100% (5B Pass) Boiling Water: 100% (5B Pass)
Hardness	ASTM D-3363	2H Pencil (Eagle)
Impact Resistance	ASTM D-2794	40 In.-lbs. Direct-No Flaking 20 In.-lbs. Reverse-No Flaking
Abrasion	ASTM D-968	Pass - Coefficient Value Min 20
Conical Mandrel	ASTM D-522	1/2" - No Flaking
Salt Spray	ASTM B-117	3000 Hrs. Pass
Humidity	ASTM D-2247	100F, 100% RH - 3000+ hours

*Film Properties were determined using 2.0 - 3.0 mils powder film over Alodine (chromated aluminum) test panels.*

## Application Data

Application Type:	Electrostatic Spray
Recommended Bake:	10 Minutes at 400 °F Metal Temperature See Cure Curve PCT-001
Specific Gravity:	1.25 ± .05
Theoretical Coverage:	154 Sq. Ft. per pound at 1.0 mil
Shelf Life from Date of Manufacture (@ 40-60% RH):	77 °F Maximum - 12 Months

*PPG recommends that all material be used in FIFO order (first in - first out). Materials that exceed the recommended shelf life should be tested prior to use.*



\* Statements and methods described herein are based upon the best information and practices known to PPG Industries, Inc. ("PPG"). Any statements or methods mentioned herein are general suggestions only and are not to be construed as representations or warranties as to safety, performance, or results. Since the suitability and performance of the product is highly dependent on the product user's processes, operations, and numerous other user-determined conditions, the user is solely responsible for, and assumes all responsibility, risk and liability arising from, the determination of whether the product is suitable for the user's purposes, including without limitation substrate, application process, pasteurization and/or processing, and end use. No testing, suggestions or data offered by PPG to the user shall relieve the user of this responsibility. PPG does not warrant freedom from patent infringement in the use of any formula or process set forth herein. Continuous improvements in coatings technology may cause future technical data to vary from what is in this bulletin. Contact your PPG representative for the most up to date information.

ENVIROCRON and the PPG logo are registered trademarks of PPG Industries Ohio, Inc.



We protect and beautify the world™

## Technical Properties

Property	Test Method	Value
Weathering		
South Florida Exposure	Minimum 5 Years	Pass
EMMAQUA NTW	Minimum 1450 MJ	Pass
Chalk Resistance	ASTM D4214A	Pass - No more than 8
Gloss Retention	ASTM D523	Pass - Minimum 30%
Color Retention	ASTM D2244	Pass - < 5.0 DE
Resistance to Erosion	ASTM D224	Pass - Less than 10% film loss
Chemical Resistance		Pass: No color change, no loss of adhesion, no blistering or no visual appearance change
Muriatic Acid	15 minute spot test	
Mortar	24 hour pat test	
Nitric Acid	30 minute vapor test	
Detergent Immersion	38C for 72 hours	
Window Cleaner	10 drops for 24 hours	



\* Statements and methods described herein are based upon the best information and practices known to PPG Industries, Inc. ("PPG"). Any statements or methods mentioned herein are general suggestions only and are not to be construed as representations or warranties as to safety, performance, or results. Since the suitability and performance of the product is highly dependent on the product user's processes, operations, and numerous other user-determined conditions, the user is solely responsible for, and assumes all responsibility, risk and liability arising from, the determination of whether the product is suitable for the user's purposes, including without limitation substrate, application process, pasteurization and/or processing, and end use. No testing, suggestions or data offered by PPG to the user shall relieve the user of this responsibility. PPG does not warrant freedom from patent infringement in the use of any formula or process set forth herein. Continuous improvements in coatings technology may cause future technical data to vary from what is in this bulletin. Contact your PPG representative for the most up to date information.

ENVIROCRON and the PPG logo are registered trademarks of PPG Industries Ohio, Inc.